United States Patent [19]

Claxton, III et al.

[54]	FIELI VERT	D-SERV ICAL T	ICEABLE SOLIDS-HANDLING URBINE PUMP
[75]	Invent	ors: Ern Eug	nest J. Claxton, III, Cornelia; gene F. Poser, Toccoa, both of Ga.
[73]	Assign	ee: Pat	terson Pump Co., Toccoa, Ga.
[21]	Appl. I	No.: 321,	,857
[22]	Filed:	Oct	. 14, 1994
[51] [52] [58]	U.S. C. Field o	l f Search	
56]		R	eferences Cited
U.S. PATENT DOCUMENTS			
3,0 3,0 3,0 4,0	028,564 398,694 620,639 652,179 063,849 417,850	8/1968 11/1971 3/1972 12/1977	Forward . Lerch . Gaffal et al . Hagen . Modianos . Hacker et al
FOREIGN PATENT DOCUMENTS			
1	614622 453758 421237		France

Patent Number:

5,496,150

Date of Patent: [45]

Mar. 5, 1996

361209 7/1938 Italy .

1016097 1/1966 United Kingdom . United Kingdom.

257111 8/1986

OTHER PUBLICATIONS

Lazarkiewicz, Stephen. Impeller Pumps. Pergamon Press, pp. 213, 217 (translated from 1965 publication. Fairbanks Morse Pump Corporation. V®TSH Vertical Turbine Solids Handling Pumps, pp. 37-78. 1992. Dicmas, John L. Vertical Turbine, Mixed Flow, and Propeller Pumps, pp. 280-323. McGraw-Hill Book Company, 1987.

Primary Examiner—F. Daniel Lopez Assistant Examiner-James A. Larson

[57]

ABSTRACT

A vertical turbine pump which operates with its inlet submerged in a body of liquid to be pumped employs an impeller provided with two or three equiangularly spaced vanes and a diffuser section provided with three equiangularly spaced stationary vanes. A vertical turbine pump incorporating such a combination of impeller and diffuser vanes exhibits favorable hydraulic efficiency and smooth operation and can effectively handle liquids with entrained solids. The pump bowl bearings are part of a cartridge which is readily removed and installed through the upstream end of the pump to facilitate servicing in the field.

14 Claims, 4 Drawing Sheets